


**Product information**

Product	<b>REGUPOL cargo tool RHK</b> squared timber
Material	SBR/NBR-based anti-slip mat <b>REGUPOL cargo mat 7210</b> <sup>®</sup> , squared timber
Delivery form	No. of units on request
Dimensions	Timber: 2400 x 100 x 60 mm Regupol anti-slip mat: 2400 x 100 x 8 mm Other dimensions on request
Usage	For use under precast concrete parts, loose pipes, pipe packages, steel girders, reinforcing steel mesh and other non-palletized cargos
Weight*	10 kg
Application field	Load securing for HGVs
Maximum load**	250 t/m <sup>2</sup> = 2.50 N/mm <sup>2</sup> at 8 mm thickness
Certification	 Cradle to Cradle Certified <sup>®</sup> is a registered trademark of the Cradle to Cradle Products Innovation Institute. <b>REGUPOL cargo tool RHK</b> <sup>®</sup> is Cradle to Cradle Certified <sup>®</sup> at the Bronze level.

\* The weights indicated are subject to fluctuations of up to 5 %  
 \*\* Based on DIN EN ISO 3386-2. Test sample size 60 x 60 mm

**Properties of the anti-slip mat used**

Colour	black with green, bright green and yellow coloured particles
Temperature resistance	-40°C to + 120°C

Physical properties	Norm	Result	Remarks
Resistance	In-house testing	UV light, sodium chlor-ide, weak acids & alkaline solutions	Please note: swelling possible on contact with hydrocarbons such as oils, fuels, etc.

Handling and Use	Norm	Result	Remarks
Resistance		Simple cleaning	Shaking, vacuuming or, if necessary, washing with a high-pressure cleaner
Discard status	Testing by VDZ Dortmund	Suitable for repeated use	Mats should be discarded when torn, split or crushed and after contact with oils, fuels, chemicals etc.
Disposal	Waste code 070299 acc. to EWC		Disposal in accordance with official and local regulations

Subject to changes in the technical data. All of the specified values are subject to fluctuation tolerances of ± 10 %.  
 The information on our called below Homepage is decisive for the up-to-dateness of the data.